

# SPECIFICATION

## IMAGE TRANSFORMATION APPARATUS AND IMAGE TRANSFORMATION PROGRAM STORAGE MEDIUM

5

### BACKGROUND OF THE INVENTION

#### Field of the Invention

The present invention relates to an image transformation apparatus for performing a transformation processing for outputting a color image by an image output device such as a color printer, and an image transformation program storage medium storing an image transformation program which causes a computer system to operate as such an image transformation apparatus.

#### 15 Description of the Related Art

Hitherto, to perform a color printing using a color printing machine, prior to performing the color printing, a proof image, which is closely similar in color to a color image to be printed by the color printing machine, is printed out using a color printer and the like. To produce such a proof image, the proof image is outputted in accordance with image data for a printer obtained such a manner that a printing profile describing a relation between image data and colors of the actual printed matter, associated with a sort of a printing machine to be used and use conditions of the printing machine (conditions necessary for a certain printing, including a sort of ink

to be used and a material of paper; and a sort of a  
printing machine, is referred to as a printing condition),  
and a printer profile describing a relation between image  
data and colors of the actually outputted proof image,  
5 associated with a sort of a printer for outputting the  
proof image and use conditions of the printer (conditions  
necessary for outputting a certain proof image, including a  
sort of a printer, is referred to as a printer condition),  
are determined, and the image data for a printing is  
10 subjected to a color conversion processing in accordance  
with the printing profile and the printer profile and is  
converted into a data format representative of a halftone  
dot image adapted for a color printer used for outputting  
the proof image so that the image data for a printing is  
15 converted into the image data for a printer. Thus, it is  
possible to obtain a proof image which is coincident in  
color representation with the actual printed matter.  
Usually, a printing profile associated with a typical  
printing condition is provided from a printing service  
20 trader, and a printer for a proof image output is also  
provided from a maker of the printer.

The printing profile and the printer profile are  
stored in an image transformation apparatus, and are  
controlled so as to finally obtain a proof image of a  
25 preferable color representation. In the event that the  
printing image data is converted into the printer image  
data and is outputted, usually, the controlled printing

profile and the proofer profile are combined to produce a single profile (a device link profile), so that a color conversion processing is applied to the printing image data referring to the device link profile. The image data  
5 subjected to the color conversion processing is converted into image data of a data format representative of a halftone dot image, which is adapted for a printer for outputting the proof image, and the image data thus converted is transmitted to the printer so that the printer  
10 outputs the proof image.

To output the proof image, the image translation apparatus receives raster image data from a so-called RIP (Raster Image Processor) system in which a color image produced and edited in a page description language is  
15 converted into a raster image data, and applies the color conversion processing and the conversion processing to the halftone dot image to the raster image data. With respect to the RIP system, there are known a plurality of types of RIP systems, such as an RIP system having a single function  
20 in which a color image described in a page description language is simply converted into a raster image data, and an RIP system having a function of performing the color conversion processing and the conversion processing to the halftone dot image directed to producing of the proof image,  
25 similar to the image transformation apparatus.

When it is considered that while such a plurality of types of RIP systems exist, the above-mentioned image

transformation apparatus is used, it is possible to adapt the image transformation apparatus to a various type of RIP systems in accordance with such a manner that even if an RIP system is provided with a function of the color  
5 conversion processing and the conversion processing to the halftone dot image, a multiple gradation image, which is simply converted into a raster image data before those types of processing are applied, is received from the RIP system, and the color conversion processing and the  
10 conversion processing to the halftone dot image are carried out by the image transformation apparatus.

To perform the color conversion processing and the conversion processing to the halftone dot image, while various patterns exist also on halftone dots, it is known  
15 that while halftone dots for producing a proof image are selected from among halftone dot patterns which are prepared in the image transformation apparatus beforehand, a picture quality of a color image finally obtained is greatly effected by the selected halftone dot pattern. It  
20 is not ensured that the image transformation apparatus prepares the same halftone dot pattern as that adopted in the RIP system having a function of performing the halftone dot processing. When the RIP system has a function of performing the halftone dot processing, such a desire that  
25 the function of the halftone dot processing in the RIP system is used will be happened.

Even in the even that it is acceptable to adopt

the halftone dot pattern which is not the same as the halftone dot pattern prepared in the RIP system, when the image translation apparatus receives from the RIP system image data representative of a multiple gradation image before the halftone dot processing, there is a need to process a very large capacity of image data to maintain an accuracy. This involves a gradation of the speed of processing.

#### SUMMARY OF THE INVENTION

In view of the foregoing, it is an object of the present invention to provide an image transformation apparatus capable of suitably processing both image data representative of a multiple gradation image from the host and image data representative of a halftone dot image, and an image transformation program storage medium storing an image transformation program which causes a computer system to operate as such an image transformation apparatus.

To achieve the above-mentioned object, the present invention provides an image transformation apparatus comprising: an image receiving section for receiving an image represented by digital data; an image sort discrimination section for discriminating whether the image received by said image receiving section is a halftone dot image or a multiple gradation image; an image transformation section for applying a conversion processing for the multiple gradation image to the halftone dot image

when it is decided by said image sort discrimination  
section that the image received by said image receiving  
section is the multiple gradation image; and a driver  
section for outputting an image discriminated as the  
5 halftone dot image by said image sort discrimination  
section and an image converted into the halftone dot image  
by said image transformation section to an image output  
device for outputting a visual image.

This feature makes it possible to suitably process  
10 both the multiple gradation image and the halftone dot  
image, and thereby expanding a range of the use of the  
available host system and thus enhancing general-purpose  
properties.

In the image transformation apparatus according to  
15 the present invention as mentioned above, it is preferable  
that said image receiving section receives a color image,  
and said image transformation section applies a color  
conversion processing to a color image decided by said  
image sort discrimination section that the image received  
20 by said image receiving section is the multiple gradation  
image, and applies the conversion processing for the  
multiple gradation image to the halftone dot image.

In case of a color of multiple gradation image,  
performing the color conversion processing prior to  
25 performing the conversion into the halftone dot image makes  
it possible to output a color image of a preferable color  
representation.

In the image transformation apparatus according to the present invention as mentioned above, it is acceptable that said image receiving section receives together with the image additional information indicating whether the image received by said image receiving section is the halftone dot image or the multiple gradation image, and said image sort discrimination section discriminates whether the image received by said image receiving section is the halftone dot image or the multiple gradation image in accordance with the additional information.

For example, tag information is added to a so-called TIFF form of image data. Search of the tag information makes it possible to see properties of the image data.

To discriminate whether it is concerned with the multiple gradation image or the halftone dot image, it does not care about a method of discrimination. For example, it is acceptable that the discrimination is performed through the search of the image data per se. However, in the event that additional information such as the tag information makes it possible to discriminate whether it is concerned with the multiple gradation image or the halftone dot image, the adoption of this way may bring about easy and high speed discrimination.

In the image transformation apparatus according to the present invention as mentioned above, the halftone dot image to be dealt with in the present invention is not

restricted to the binary halftone dot image, and it is acceptable that ternary or quaternary halftone dot image is concerned. Also with respect to multiple gradation image, it does not care about the number of gradations, it is acceptable that said image receiving section is adapted to receive a binary halftone dot image and a 256-gradation of multiple gradation image.

To achieve the above-mentioned object, the present invention provides an image transformation program storage medium storing an image transformation program which causes a computer system to operate as an image transformation apparatus for performing an image transformation upon receipt of an image represented by digital data, when the image transformation program is executed by the computer system, said image transformation program comprising:

an image sort discrimination section for discriminating whether the received image is a halftone dot image or a multiple gradation image;

an image transformation section for applying a conversion processing for the multiple gradation image to the halftone dot image when it is decided by said image sort discrimination section that the received image is the multiple gradation image; and

a driver section for outputting an image discriminated as the halftone dot image by said image sort discrimination section and an image converted into the halftone dot image by said image transformation section to



an image output device for outputting a visual image.

In the image transformation program storage medium according to the present invention as mentioned above, it is preferable that said image transformation program causes  
5 the computer system to operate as an image transformation apparatus for performing an image transformation upon receipt of a color image, when the image transformation program is executed by the computer system, and

wherein said image transformation section applies  
10 a color conversion processing to a color image decided by said image sort discrimination section that the received image is the multiple gradation image, and applies the conversion processing for the multiple gradation image to the halftone dot image.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a structural view of a printing and proof image producing system which an image transformation apparatus according to an embodiment of the present  
20 invention is applied to.

Fig. 2 is a view perspective view of the personal computer shown in Fig. 1 with one block.

Fig. 3 is a hardware structural view of the personal computer.

Fig. 4 is an image transformation program stored  
25 in a storage medium.

Fig. 5 is a functional block diagram of an image

transformation apparatus according to one embodiment of the present invention.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

5           Embodiments of the present invention will be described with reference to the accompanying drawings.

Fig. 1 is a structural view of a printing and proof image producing system which an image transformation apparatus according to an embodiment of the present invention is applied to.

10           A RIP system 10 receives image data (PDL data) described by a page description language (PDL), which is produced by an electronic page make-up system (not illustrated), and converts the received PDL data into  
15           raster image data for CMYK four colors, which is developed into a bit map.

20           The raster image data obtained by the RIP system 10 is fed to a film printer 20 when a printing is performed. The film printer 20 produces a CMYK four colors of printing film original plate according to the entered raster image data for printing. From the printing film original plate, a printing plate is produced and the printing plate thus produced is mounted on a printing machine 30. An ink is  
25           coated on the printing plate mounted on the printing machine 30 and is transferred to a printing paper, so that a printed image 31 is formed on the printing paper.

Such a series of process that the film printer 20

produces the printing film original plate; from the  
printing film original plate, the printing plate is  
produced and the printing plate thus produced is mounted on  
the printing machine 30; the ink is coated on the printing  
plate mounted on the printing machine 30 and is transferred  
to the printing paper; and the printed image is formed on  
the printing paper, is concerned with a very large amount  
of work and takes a much cost. Thus, before the actual  
printing work is performed, a printer 60 is used to produce  
a proof image 61 in a manner set forth below to confirm the  
finish of the printed image 31 beforehand.

To produce the proof image, the raster image data  
produced by the RIP system 10 is fed to a personal computer  
50.

The RIP system 10 may output both the raster image  
data representative of a multiple gradation image before  
the color conversion processing and the halftone dot  
processing are performed, and the raster image data  
representative of a halftone dot image after the color  
conversion processing and the halftone dot processing are  
performed. Here, it is assumed that the RIP system 10  
outputs the raster image data representative of a multiple  
gradation image, and feeds the same to the personal  
computer 50.

The personal computer 50 corresponds to one  
embodiment of the image transformation apparatus of the  
present invention. The raster image data transmitted from

the RIP system 10 to the personal computer 50 is subjected to the color conversion processing and the halftone dot processing in the personal computer 50, and is converted into raster image data for RGB three colors representative of the halftone dot image, which is adapted for the printer 60 for outputting the proof image. The printer 60 receives the data for RGB three colors and outputs the proof image 61 in accordance with the received data.

To perform the color conversion processing in the personal computer 50, color conversion conditions in the color conversion processing are controlled so that colors of the proof image obtained through printing by the printer 60 are coincident with colors of the printed image 31 obtained through printing by the printing machine 30.

To perform the halftone dot processing in the personal computer 50, a desired halftone dot pattern is selected among from a plurality of halftone dot patterns prepared beforehand.

Thus, the color conversion processing is performed under the controlled color conversion conditions, and further the halftone dot processing is performed in accordance with the selected halftone dot pattern, so that a proof image is outputted in accordance with the raster image data for RGB three colors after those processings are performed to confirm the proof image, and thereby confirming the finish of the printing beforehand.

An aspect of the embodiment of the present

invention in the printing and proof image producing system shown in Fig. 1 resides in contents of processing executed in the personal computer 50. Thus, first, there will be described hereinafter.

5            Fig. 2 is a view perspective view of the personal computer shown in Fig. 1 with one block. Fig. 3 is a hardware structural view of the personal computer.

            The personal computer 50 comprises: on an appearance basis, a main frame 51; an image display unit 52  
10    for displaying an image on a display screen 52a in accordance with an instruction from the main frame 51; a keyboard 53 for inputting various sorts of information according to the key operation to the main frame 51; and a mouse 54 for inputting an instruction according to an icon  
15    or the like displayed at a designated position on the display screen 52a. The main frame 51 has a floppy disk loading slot 51a for loading a floppy disk, and a CD-ROM loading slot 51b for loading a CD-ROM.

            The main frame 51 incorporates therein, as shown  
20    in Fig. 3, a CPU 511 for executing various sorts of programs, a main memory 512 in which a program stored in a hard disk device 513 is read out and developed for execution by the CPU 511, the hard disk device 513 storing various sorts of programs and data, a floppy disk drive 514  
25    for driving a floppy disk 100, a CD-ROM drive 515 for driving a CD-ROM 110, an input interface 516 connected to the RIP system 10 (cf. Fig. 1) for receiving image data

from the RIP system 10, and a printer interface 517 for sending image data to the printer 60 for a proof image output. Those elements are connected via a bus 55 with the image display unit 52, the keyboard 53 and the mouse 54.

5           The CD-ROM 110 stores an image transformation program which causes the personal computer 50 to operate as an image transformation apparatus, and is loaded onto the CD-ROM drive 515. The image transformation program stored in the CD-ROM 110 is up-loaded onto the personal computer  
10           50 and is stored in the hard disk device 513.

          Fig. 4 is an image transformation program stored in a storage medium.

          A storage medium 70 is typical of the CD-ROM 110 shown in Fig. 3, the floppy disk 100, and the hard disks in  
15           the hard disk device 513. The CD-ROM 110 storing an image transformation program 700 corresponds to an embodiment of the image transformation program storage medium of the present invention. When the image transformation program 700 stored in the CD-ROM 110 is up-loaded onto the personal  
20           computer 50 and is stored in the hard disk device 513, the hard disk of the hard disk device 513 also corresponds to an embodiment of the image transformation program storage medium of the present invention. When the image transformation program stored in the hard disk device 513  
25           is down-loaded onto the floppy disk 100, the floppy disk 100 storing the image transformation program also corresponds to an embodiment of the image transformation

program storage medium of the present invention.

The image transformation program 700 has an image sort discrimination section 701, an image transformation section 702, a control section 703, and a driver section 704. The image transformation section 702 includes a color conversion processing section 702a and a halftone dot processing section 702b. Those parts of Fig. 4 are denoted by the same names as those of Fig. 5 but different in reference numbers. The explanation of those parts will be described in conjunction with Fig. 5 directed to an image transformation apparatus. It is noted, however, that while those parts of the image transformation apparatus are each complex of the hardware and the software of the personal computer 50 shown in Fig. 1 to 3, the image transformation program shown in Fig. 4 is concerned with only part of the software of the hardware and the software.

Fig. 5 is a functional block diagram of an image transformation apparatus according to an embodiment of the present invention.

An image transformation apparatus 80 comprises the personal computer 50 shown in Fig. 1 to 3 and an image transformation program to be executed in the personal computer 50. The image transformation apparatus 80 comprises an image receiving section 81, an image sort discrimination section 82, an image transformation section 83, a driver section 84 and a control section 85.

The image receiving section 81 receives a color

image represented by raster image data for CMYK four colors generated by the RIP system 10. On a hardware basis, the input interface 516 shown in Fig. 516 corresponds to the image receiving section 81.

5           According to the present embodiment, the RIP system 10 produces a TIFF type of multiple gradation color image (here 256 gradation of color image) and a binary halftone dot color image, which are simultaneously fed to the image transformation apparatus 80, or alternatively  
10           only any one of which is fed to the image transformation apparatus 80.

          The image sort discrimination section 82 discriminates whether the color image received by the image receiving section 81 is the binary halftone dot color image  
15           or the 256 gradation of color image.

          According to the present embodiment, the RIP system 10 produces raster image data representative of a TIFF type of halftone dot image or multiple gradation image, which are fed to the image transformation apparatus 80. As  
20           shown in Fig. 5, tag information 91 is added to the TIFF type of image 90. On the tag information 91, there is recorded discrimination information for discriminating whether the received color image is the 2 gradation of image or the 256 gradation of image. Thus, the image sort  
25           discrimination section 82 discriminates the sort of the received image by referring to the tag information. In the event that the multiple gradation image is determined, the



image is transmitted to the image transformation section 83.  
On the other hand, in event that the halftone dot image is  
determined, the image is transmitted to the driver section  
84.

5           On a hardware basis, the CPU 511 executing the  
image sort discrimination section 701 (cf. Fig. 4)  
corresponds to the image sort discrimination section 82.

10           When the image transformation section 83 receives  
a multiple gradation image from the image sort  
discrimination section 82, a color conversion processing  
section 83a applies a color conversion processing to the  
multiple gradation image, and a halftone dot processing  
section 83b applies a halftone dot processing to the  
multiple gradation image after the color conversion  
15           processing so as to produce a halftone dot image, and  
transmits the halftone dot image (raster image data  
representative of the halftone dot image) thus produced to  
the driver section 84.

20           On a hardware basis, the CPU 511 executing the  
image transformation section 702 (cf. Fig. 4) corresponds  
to the image transformation section 83.

25           The driver section 84 outputs halftone dot image  
(raster image data for RGB three colors) after converted by  
the image transformation section 83 to the printer 60. On  
a hardware basis, the CPU 511 by which a driver software  
(the driver section 704 for the image transformation  
program shown in Fig. 4) is executed, and the printer

interface 517 for sending image data to the printer 60  
correspond to the driver section 84.

The control section 85 produces in accordance with  
an operation of an operator data for controlling color  
conversion conditions when the color conversion processing  
section 83a performs a color conversion processing, and  
transmits the data to the color conversion processing  
section 83a.

Further, the control section 85 selects a halftone  
dot pattern in accordance with an operation of an operator,  
and informs the halftone dot processing section 83b of a  
matter as to which halftone dot pattern is selected. As  
result, the halftone dot processing section 83b performs  
the halftone dot processing in accordance with the received  
halftone dot pattern.

Accordingly, on the a hardware basis, the keyboard  
53 and the mouse 54 shown in Figs. 2 and 3, and the CPU 511  
executing the control section 703 of the color conversion  
program shown in Fig. 4 correspond to the control section  
85.

In this manner, in the image transformation  
apparatus 80, the image sort discrimination section 82  
discriminates whether an image represented by the raster  
image data, which is transmitted from the RIP system 10, is  
a halftone dot image or a multiple gradation image. When  
it is decided as the multiple gradation image, the image is  
transmitted to the image transformation section so as to be

subjected to the color conversion processing and the halftone dot processing, and then transmitted to the driver section 84. On the other hand, when it is decided as the halftone dot image, the halftone dot image is directly transmitted to the driver section 84 bypassing the image transformation section 83. Thus, it is possible to couple a various type of RIP systems to the image translation apparatus as the RIP system 10 which is the host system, and thereby implementing an image translation apparatus having a high general-purpose properties.

Incidentally, according to the present embodiment as mentioned, while it is explained that the halftone dot image is a binary halftone dot image, the halftone dot image to be dealt with in the present invention is not restricted to the binary halftone dot image, and it is acceptable that ternary or quaternary halftone dot image is concerned as far as it is suitable for the printer 60.

Similarly, according to the present embodiment as mentioned, while it is explained that the multiple gradation image is of 256 gradations, the multiple gradation image to be dealt with in the present invention is not restricted to the multiple gradation image of 256 gradations, and it is acceptable that a multiple gradation image of other gradations, for example, 128 gradations and 1024 gradations, is concerned.

Further, in the above-description, while it is explained that the TIFF type of raster image data is dealt

with, the present invention is not restricted to the TIFF type of raster image data.

As mentioned above, according to the present invention, it is possible to suitably process both the multiple gradation image and the halftone dot image, and thereby expanding a range of the use of the available host system and thus enhancing general-purpose properties.

While the present invention has been described with reference to the particular illustrative embodiments, it is not to be restricted by those embodiments but only by the appended claims. It is to be appreciated that those skilled in the art can change or modify the embodiments without departing from the scope and spirit of the present invention.